a fitre

FITRE S.p.A. • DSI Division

Head Office and Production Plant: 20142 Milano • Italy • via Valsolda, 15 phone: +39 02 8959 01 • fax: +39 02 8959 0400 e-mail: divisione.dsi@fitre.it

TAS26D

20241018/10:03

Indoor, weatherproof and explosion-proof phones (analog & VoIP)

P/N 7137121

notice

in questa pubblicazione non sono impegnativi e possono venire modificati senza preavviso. The information contained in this publication are not binding and are subject to change

riportati

dati

Weatherproof analog ACB telephone with display for indoor and outdoor use.

The TAS26D telephone is as stylish for indoor use as it is resistant for outdoor use in areas without explosive atmospheres.

Its modern design is the perfect "packing" for the finest high-tech and its striking signal colours ensure that TAS26D cannot be missed whenever a telephone is urgently needed, e.g. in case of an emergency in poor weather and light conditions.

The TAS26D is suitable for almost universal use thanks to its amazing transformability. A deft hand movement and the desk telephone for indoor use is converted into a wall telephone for outside use. The stylish housing is made of impact-resistant and shockproof plastic moulding.


Even acids, alkalis or lubricants cannot damage the high-quality components of our new versatile desk/wall telephone.

- Sturdy and impact-resistant polycarbonate case
- Shock-resistant
- Chemical-resistant
- IP65 protection
- Full 12-key keyboard
- PIN code
- Display with 2 lines, 16 positions per row, 7x5 matrix pictograms, 4 languages
- Ringing volume: ≥95dB(A) at 1m distance
- Supply voltage: 24÷66VDC
- Supply current: 19÷100mA
- Ringing alternating current: 19÷68Hz
- Ringing frequency: 18÷68Hz
- Mouthpiece: electret-foil microphone
- Yellow, red, grey or black colour
- Shock-resistant
- Chemical-resistant
- Lockable handset with stabilization bracket (option)
- Cable glands: 1x M20 cable gland, 1x M20 blind plug, 2x M12 blind plugs



HANDSET DESK/WALL MOUNTING IP65

- 25°C to + 55°C



dimensions (W x H x D) 191,0 x 293,0 x 128,0 mm weight 1,7 kg

To explore our wide range of products and to verify their conformity with your requirements, we invite you to visit our website **fitresistemi.com**

CommunicationsFirst

www.fitre.it

