

FITRE S.p.A. • Divisione DSI

20142 Milano • Italia • via Valsolda, 15 telefono: (+39) 02.8959.01 • telefax: (+39) 02.8959.0400 e-mail: divisione.dsi@fitre.it

The TONO BL is the must advanced realization of standard local battery telephone sets, suitable for point to point direct connections.

Strong but elegant and ergonomic execution suitable both for desk mounting and wall mounting, equipped with advanced electronic that allows very useful facilities.

The handset is equipped with a wheel for the volume reception level and with a LED that lights during the call ring signal.

The hook is magnetic type, without any mechanical movement.

The call generator is static type: the call is made pushing the relevant push button.

A LED on the telephone set base, signals the situation "ON" when the handset is picked up and, too, the battery charge condition: pushing the call push-button this LED switch off if the battery level is less than 2,4V.

The electronic bell volume can be regulated by a lever on the left side of the telephone set base.

The TONO BL accept a power supply between 2,4 and 4,5Vdc.

FITRE has realized two kinds of power supply specially for the TONO:

code 7122201: a small box suitable for inserting n.3 standard torch batteries 1,5V, type D-LR20.
code 7715110: small box with built-in a 220Vac, 24Vdc rectifier and a 4V rechargeable battery.

Dimensions: 58 x 122 x 83 mm.





TONO BL

ELECTRONIC LB TELEPHONE SET

TECHNICAL DATA

Antishock resin made case		
Power supply:	2,4 to 4,5Vdc	
Receiving caps:	dynamic type	
Microphone :	electret type	
Output level:	+6dB on 600 ohm	
Range 20 dB of the receiving volume regulation		
Bell intensity:	70dB at 1m	
Call generator able to call till 8 "TONO BL" in parallel		
Protection against short circuits, noises on the lines, etc.		
Colours:	base black, handset red	
Dimensions:	250 x 100 x 50mm	
Weight:	800 g	

Model list	code
TONO BL	7122240