

CB (Central Battery) and LB (Local Battery) phones

P/N 7147102

Portable LB (Local Battery) amplified weatherproof handset fitted with a piezo-electric element for voice transmission.
The handset unit is equipped with a call signal generator and a voice sending amplifier.

HIGHLIGHTS

- Suitable for severe environments with high temperature and high humidity
- No external power supply is necessary for communication
- Drip-proof construction
- 1x grey CALL button • 1x black TALK button
- 2x 'AA' 1,5V batteries required (not included)
- Power consumption: 120mA (talk); approx. 5mA (call)
- Call signal: 1000÷1500Hz • I/O impedance: 600Ω
- Telephone cable diameter: 0,75mm (or larger)
- Distance up to 3km in one-to-one connection

OPERATING MODE

1. To start a communication, press the CALL button (grey) so that the calling signal is transmitted to the other user (at the same time you will also hear the buzzer sound from you handset).
2. The other user, being signalled by the buzzer, answers the call by pressing the CALL button too.
3. Afterwards, both users simultaneously press the TALK button (black) to start a conversation. While the CALL button is pressed down at both sides, the conversation can be held just like an ordinary telephone call.

Note: when more than 2 handphone units are hooked up on the communication line, a unique signalling code may be used, therefore the calling unit can be identified by the buzzer signal.

ACCESSORIES

- Jack plug - P/N 2964156 • Socket - P/N 2964088
- Clamp TS105 - P/N 8319825 • Cable TS104 - P/N 8319826
- Carrying bag - P/N 8319812


-- NOTE --

If necessary, an additional external ringer such as the TRILLO 201T/E (P/N 7322255) can be connected to the TLP97.



HANDSET

IP66



dimensions (W x H x D) 73,0 x 246,0 x 77,0 mm
weight 750 g

