a fitre

FITRE S.p.A. • DSI Division

Head Office and Production Plant: 20142 Milano • Italy • via Valsolda, 15 phone: +39 02 8959 01 • fax: +39 02 8959 0400 e-mail: divisione.dsi@fitre.it

TAS26 Z2

20250423/14:42

Indoor, weatherproof and explosion-proof phones (analog & VoIP)

P/N 7137126

notice

riportati in questa pubblicazione non sono impegnativi e possono venire modificati senza preavriso. The information contained in this publication are not binding and are subject to change

dati

Explosion-proof analog ACB telephone outdoor use

The TAS26 Z2 is a stylish telephone for outdoor use, suitable for ATEX certified explosion-proof areas (Zones 2 - 22).

Its modern design is the perfect "packing" for the finest high-tech and its striking signal colours ensure that TAS26 Z2 cannot be missed whenever a telephone is urgently needed, e.g. in case of an emergency in poor weather and light conditions.

The TAS26 Z2 is suitable for almost universal use thanks to its amazing transformability. A deft hand movement and the desk telephone for indoor use is converted into a wall telephone for outside use. The stylish housing is made of impact-resistant and shockproof plastic

Even acids, alkalis or lubricants cannot damage the high-quality components of our new versatile desk/wall telephone.


- ATEX certified for Zones 2 22:
- II 3G Ex nA L IIC T5

moulding.

- II 3D Ex tD A22 IP65 80°C
- Sturdy polycarbonate case
- Shock-resistant
- Chemical-resistant
- IP65 protection
- Full 12-key keyboard
- No display
- Ringing volume ≥ 95dB(A) in 1m distance
- Supply voltage: 24÷66VDC
- Supply current: 19÷100mA
- Ringing alternating current: 19÷68Hz
- Ringing frequency: 18÷68Hz
- Mouthpiece: electret-foil microphone
- Shock-resistant
- Chemical-resistant
- Lockable handset with stabilization bracket (option)
- Yellow, red, grey or black colour



HANDSET DESK MOUNTING IP65 ATEX - 20°C to + 55°C



dimensions (W x H x D) 191,0 x 293,0 x 128,0 mm weight 2,3 kg



CommunicationsFirst

www.fitre.it



943 —